



ELITE DAISY DIRECT / INDIRECT

LED

Suspended Lighting Fixtures With Lens

Luminaire Suspendus Avec Lentille

APPLICATION AREAS

Shopping Malls
Supermarkets
Offices
Meeting rooms
Stores
Hospitals
Schools
Corridors

DOMAINES D'UTILISATION

Centres Commerciaux
Supermarchés
Bureaux
Salles de Réunions
Magasins
Hopitaux
Ecoles
Couloirs

BODY

Anodized aluminum with satin finishing. Black and white color options with elegant design.

LENS

With 50° or 80° lens.

DIFFUSER

UV stabilized frosted diffuser.

CONVERTER

Compatible with ENEC standards.

LED

LED modules with 60.000 hours lifetime LUMILEDS / SAMSUNG / NICHIA brand LEDs.

SUSPENSION

Composed of 1mm steel wire rope and nickel-plated brass components. Suspension height is adjustable. Supplied with transparent electric cord and ceiling mounted electrical junction box with aesthetic design.

CORPS

Corps en aluminium anodisé, satiné. Design élégant. Couleurs blanc, noir disponibles.

LENS

Avec lentille 50 ° ou 80 °.

DIFFUSEUR

Diffuseur givré. Anti UV.

CONVERTEUR

Convertisseur, conforme aux normes ENEC.

LED

Modules LED – Durée de vie 60.000 heures avec LED de marque LUMILEDS / SAMSUNG / NICHIA.

SYSTEME DE FIXATION

Composé d'un fil en acier de 1mm, de composants en laiton nickelés. Livré avec un cordon électrique transparent et une boîte de jonction électrique à fixer au plafond. Hauteur de fixation réglable.

NOTE

Lumen values are based on white body color measurements. Depending on different body colors lumen values may drop. For instance, there will be 9% drop for black body color.

V / Hz 220 - 240 / 50 - 60

Options

Dimmable electronic ballast or convertor.
Emergency kit

Options

Ballast électronique dimmable ou convertisseur.
Kit d'urgence.

NOTE

Given lumen values are net delivered luminaire output lumens.


Given power values are total consumed AC power of the luminaire.

NOTE

Les valeurs de lumens données sont les lumens de sortie nets du luminaire.

Les valeurs de puissance données sont la puissance AC totale consommée du luminaire.

Indirect Lighting
Éclairage Indirect



Direct Lighting
Éclairage Direct



Color Options
Options de Couleur



Direct / LED Type / Type LED



Color Rendering Index / Indice de Rendu des Couleurs: (CRI): Ra>80

Code	Power Puissance (W)	LED Type Type De LED	LED Module Module LED	Lum. Flux Flux Lum. (lm)	Color Temperature Température De Couleur (K)	Dimensions (mm)			Weight Poids (kg)	Packing Quantity Colisage	Pcs./20" Container Pcs./20" Conteneur
						a	l	h			
PL10S12L15L	16	2835 SMD	PCB	1935	2700 - 6500	47	578	73	1.2	2	3635
PL10S13L15L	22	2835 SMD	PCB	2900	2700 - 6500	47	858	73	1.7	2	3635
PL10S14L15L	29	2835 SMD	PCB	3865	2700 - 6500	47	1138	73	2.3	2	2835
PL10S15L15L	37	2835 SMD	PCB	4830	2700 - 6500	47	1418	73	2.9	2	2295
PL10S16L15L	44	2835 SMD	PCB	5800	2700 - 6500	47	1698	73	3.5	2	1970
PL10S17L15L	52	2835 SMD	PCB	6765	2700 - 6500	47	1978	73	4.0	2	1560
PL10S18L15L	60	2835 SMD	PCB	7730	2700 - 6500	47	2258	73	4.6	2	1560
PL10S19L15L	66	2835 SMD	PCB	8695	2700 - 6500	47	2538	73	5.2	2	1560
PL10S10L15L	75	2835 SMD	PCB	9660	2700 - 6500	47	2818	73	5.7	2	1255


In-Direct / LED Type / Type LED

Color Rendering Index / Indice de Rendu des Couleurs: (CRI): Ra>80

Code	Power Puissance (W)	LED Type Type De LED	LED Module Module LED	Lum. Flux Flux Lum. (lm)	Color Temperature Température De Couleur (K)	Dimensions (mm)			Weight Poids (kg)	Packing Quantity Colisage	Pcs./20" Container Pcs./20" Conteneur
						a	l	h			
PL10ES21L15L	16/8	2835 SMD	PCB	1935/665	2700 - 6500	47	578	73	1.3	2	3635
PL10ES32L15L	22/14	2835 SMD	PCB	2900/1330	2700 - 6500	47	858	73	1.8	2	3635
PL10ES43L15L	29/21	2835 SMD	PCB	3865/1995	2700 - 6500	47	1138	73	2.4	2	2835
PL10ES54L15L	37/26	2835 SMD	PCB	4830/2660	2700 - 6500	47	1418	73	3.0	2	2295
PL10ES65L15L	44/33	2835 SMD	PCB	5800/3325	2700 - 6500	47	1698	73	3.8	2	1970
PL10ES76L15L	52/39	2835 SMD	PCB	6765/3990	2700 - 6500	47	1978	73	4.3	2	1560
PL10ES87L15L	60/47	2835 SMD	PCB	7730/4655	2700 - 6500	47	2258	73	4.9	2	1560
PL10ES98L15L	66/53	2835 SMD	PCB	8695/5320	2700 - 6500	47	2538	73	5.8	2	1560
PL10ES109L15L	75/60	2835 SMD	PCB	9660/5985	2700 - 6500	47	2818	73	6.3	2	1255



80° Light Beam



50° Light Beam



pamir
lighting