

DOWNLIGHT

LED

Adjustable Surface Mounted Downlight

Réglable Apparents Downlight

APPLICATION AREAS	DOMAINES D`UTILISATION
Shopping Malls	Centres Commerciaux
Supermarkets	Supermarchés
Offices	Bureaux
Meeting rooms	Salles de Réunion
Stores	Magasins
Hospitals	Hopitaux
Schools	Ecoles
Corridors	Couloirs

BODY
Aluminum profile frame and injection head.

REFLECTOR
High-purity aluminum reflector; narrow, medium and wide angle options.

CONVERTER
Long life, low power loss converter with constant current. Compatible with ENEC standards.

LED
LED modules with 60.000 hours lifetime SAMSUNG / OSRAM / PHILIPS brand LEDs.

CORPS
Profilé en aluminium et tête d'injection.

REFLECTEUR
Réflecteur en aluminium de haute pureté; options d'angle étroit, moyen et large.

CONVERTEUR
Converteur, conforme aux normes ENEC. Longue vie. Perte de puissance faible avec courant constant.

LED
Modules LED – Durée de vie 60.000 heures avec LED de marque SAMSUNG / OSRAM /PHILIPS.

V / Hz	220 - 240 / 50 - 60
Options	**Options**
Dimmable electronic ballast or convertor. Emergency kit for models with LED	Ballast electronique dimmable ou converteur. Kit d`urgence pour les modéles LED.

NOTE	NOTE
Given lumen values are net delivered luminaire output lumens. Given power values are total consumed AC power of the luminaire.	Les valeurs de lumens données sont les lumens de sortie nets du luminaire. Les valeurs de puissance données sont la puissance AC totale consommée du luminaire.

IP 40 TS 8698 EN 60598-2-1



LED Type / Type LED

Color Rendering Index / Indice de Rendu des Couleurs: (CRI): Ra>80

Code	Power Puissance (W)	Led Type Type De Led	Lum. Flux Flux Lum. (lm)	Color Temperature Température De Couleur (K)	Dimensions (mm) a	b	h	Weight Poids (kg)	Packing Quantity Colisage	Pcs./20″Container Pcs./20″ Conteneur
PLD3U09C	9	COB	630	2700 - 6500	97	97	100	1,50	24	20710
PLD3U17C	17	COB	1255	2700 - 6500	197	97	100	3,20	12	10850
PLD3U25C	25	COB	1890	2700 - 6500	292	97	100	4,70	8	7350









