

VEGA

LED

Suspended Lighting Fixtures With Frosted Diffuser

Luminaires Suspendus Avec Diffuseur Givré

APPLICATION AREAS

Shopping Malls
Supermarkets
Offices
Meeting rooms
Stores
Hospitals
Schools
Corridors

DOMAINES D`UTILISATION

Centres Commerciaux
Supermarchés
Bureaux
Salles de Réunions
Magasins
Hopitaux
Ecoles
Couloirs

BODY
Anodized aluminum with satin finishing. Black and white color options with elegant design.

DIFFUSER
UV stabilized frosted diffuser.

CONVERTER
Long life, low power loss converter with constant current. Compatible with ENEC standards.

LED
LED modules with 60.000 hours lifetime LUMILEDS / SAMSUNG / NICHIA brand LEDs.

SUSPENSION
Composed of 1mm steel wire rope and nickel-plated brass components. Suspension height is adjustable. Supplied with transparent electric cord and ceiling mounted electrical junction box with aesthetic design

CORPS
Corps en aluminium anodisé, satiné. Design elégant. Couleurs blanc, noir disponibles.

DIFFUSEUR
Diffuseur givré. Anti UV.

CONVERTEUR
Converteur, conforme aux normes ENEC. Longue vie. Perte de puissance faible avec courant constant .

LED
Modules LED – Durée de vie 60.000 heures avec LED de marque LUMILEDS / SAMSUNG / NICHIA.

SYSTEME DE FIXATION
Composé d`un fil en acier de 1mm , de composants en laiton nickelés. Livré avec un cordon electrique transparent et une boite de jonction electrique á fixer au plafond. Hauteur de fixation réglable.

IP 40 TS 8698 EN 60598-2-1

Color Options
Options de Couleur



LED Type / Type LED

Color Rendering Index / Indice de Rendu des Couleurs: (CRI): Ra>80

Code	Power Puissance (W)	LED Type Type De LED	LED Module Module LED	Lum. Flux Flux Lum. (lm)	Color Temperature Température De Couleur (K)	Dimensions (mm) a	l	h	Weight Poids (kg)	Packing Quantity Colisage	Pcs./20″ Container Pcs./20″ Conteneur
PL7S12L15C	14	2835 SMD	PCB	1465	2700 - 6500	70	570	90	1.9	4	2910
PL7S12L25C	21	2835 SMD	PCB	2195	2700 - 6500	70	570	90	2.0	4	2910
PL7S13L15C	21	2835 SMD	PCB	2195	2700 - 6500	70	850	90	2.5	4	2910
PL7S13L25C	30	2835 SMD	PCB	3295	2700 - 6500	70	850	90	2.6	4	2910
PL7S14L15C	26	2835 SMD	PCB	2930	2700 - 6500	70	1130	90	3.1	4	2270
PL7S14L25C	41	2835 SMD	PCB	4390	2700 - 6500	70	1130	90	3.2	4	2270
PL7S15L15C	33	2835 SMD	PCB	3660	2700 - 6500	70	1412	90	3.7	4	1840
PL7S15L25C	51	2835 SMD	PCB	5490	2700 - 6500	70	1412	90	3.8	4	1840
PL7S16L15C	39	2835 SMD	PCB	4390	2700 - 6500	70	1693	90	4.3	4	1575
PL7S16L25C	61	2835 SMD	PCB	6585	2700 - 6500	70	1693	90	4.4	4	1575
PL7S17L15C	47	2835 SMD	PCB	5120	2700 - 6500	70	1973	90	4.9	4	1250
PL7S17L25C	70	2835 SMD	PCB	7680	2700 - 6500	70	1973	90	5.1	4	1250
PL7S18L15C	53	2835 SMD	PCB	5855	2700 - 6500	70	2254	90	5.5	4	1250
PL7S19L15C	60	2835 SMD	PCB	6585	2700 - 6500	70	2534	90	6.1	4	1250
PL7S10L15C	66	2835 SMD	PCB	7315	2700 - 6500	70	2815	90	6.7	4	1000



V / Hz	220 - 240 / 50 - 60


Options	Options
Dimmable electronic ballast or convertor. Emergency kit	Ballast electronique dimmable ou converteur. Kit d`urgence.

NOTE

Lumen values are based on white body color measurements. Depending on different body colors lumen values may drop. For instance, there will be 20% drop for black body color.

NOTE

Les valeurs de lumens sont basées sur des mesures de couleur de corps blanche. En fonction des différentes couleurs de corps, les valeurs de lumens peuvent diminuer. Par exemple, il y aura une baisse de 20% pour la couleur de corps noire.



NOTE	NOTE
Given lumen values are net delivered luminaire output lumens. Given power values are total consumed AC power of the luminaire.	Les valeurs de lumens données sont les lumens de sortie nets du luminaire. Les valeurs de puissance données sont la puissance AC totale consommée du luminaire.